



自带保险丝固态继电器系列 专利产品



主要技术参数	产品型号	SAP4805D-F SAP4810D-F SAP4815D-F SAP4820D-F SAP4825D-F SAP4840D-F SAP4860D-F SAP4860D-F SAP4870D-F SAP4880D-F SAP4805A-K SAP4810A-K SAP4815A-K SAP4820A-K SAP4825A-K SAP4840A-K SAP4860A-K SAP4860A-K SAP4870A-K SAP4880A-K SAP4805D-K SAP4810D-K SAP4815D-K SAP4820D-K SAP4825D-K SAP4840D-K SAP4860D-K SAP4860D-K SAP4870D-K SAP4880D-K
负载电压 Load voltage	40-530VAC	
负载最大电流 Max Load current	5A、10A、15A、20A、25A、40A	50A、60A、70A、80A
隔离电压 Isolation bet. In & out	≥2500VAC 1min	
绝缘电压 Isolation to case	≥2500VAC 1min	
控制电压 Control voltage	3-32VDC	
控制电流 Control current	6-25mA (内置恒流电路)	
通态压降 Turn-on voltage	≤1.3VAC	
断态漏电流 off-state leakage	≤3mA	
电压上升率 off-state dv/dt	500V/μs	
通断时间 on or off time	10ms	
频率范围 Frequency range	47/63Hz	
动作状态指示 Status indicator	单LED指示/双LED指示	
工作环境温度 Operating temperature	-40 ~ 80°C	

外形尺寸 Dimensions:

